Barrier Coating for Application onto Hot Surfaces





Two-component Belzona 5841 is a barrier coating for the protection of metallic surfaces.

It has been specifically formulated for application to manually prepared surfaces on equipment which cannot be taken out of service.

This solvent-free material is designed for direct application onto equipment operating in elevated temperature service (30-80°C / 86-176°F).

TECHNICAL DATA	Mixing ratio (Base : Solidifier)	4 : 1 by volume	8.5 : 1 by weight	
	Working life	60 minutes at 20°C (68°F)		
	Shelf life	5 years		
	Adhesion (Tensile shear)	Grit blasted / ground steel: 24.1 MPa (3,500 psi)		
	Adhesion (pull-off)	Grit blasted / ground steel: 12.4 MPa (1,800 psi)	Rusty steel prepared to ISO 8501-1 St 3: 9.65 MPa (1,400 psi)	
	Heat distortion temperature	95°C (203°F) after 7 days cure at 80°C (176°F)	51°C (123°F) after 7 days cure at 20°C (68°F)	

CURE TIMES	Temperature	30°C (86°F)	50°C (122°F)	80°C (176°F)
	Touch dry/light loading	2½ hours	1 hour	20 mins
	Full cure	24 hours	16 hours	8 hours

*Please consult the Product Specification Sheet (PSS) and Instructions for Use (IFU) for the latest technical data.



EASY TO APPLY



HIGH TEMP CURE



CORROSION RESISTANT



TOLERANT TO SURFACE PREPARATION

5000 Series BELZONA 5841



Key Benefits:

Lasting protection

Continuous protection with excellent chemical, impact and abrasion resistance.

• System for varied temperature service

Can be applied overlapping with Belzona 5831 and Belzona 5851 to cover the range of service temperatures between 10°C/50°F and 150°C/302°F.

• Easy to Apply

Specialist tools are not required to apply Belzona 5841. It is also tolerant to surface preparation.



Belzona 5841 used for pipe corrosion protection

Application Areas:

- Absorbers
- Columns
- District heating
- Evaporators
- Flare drums
- Heat exchangers
- Hot wells
- Nozzles
- Pipework
- Scrubbers
- Strippers
- Vessels

Before & After:



For more information, please contact your local Belzona representative:

QUALITY PRODUCTS - TECHNICAL SUPPORT

Belzona products are manufactured under an ISO 9001 Registered Quality Management System.

Belzona has a global distribution network of over 140 Distributors operating in 120 countries. Local support is provided by a trained Technical Consultant who will diagnose the problem, recommend the solution and provide 24-hour, on-site application supervision and advice.